

# STEEL

Material  
**Alloyed Chromalloy**

External treatment  
**Shotblasting with selected grit, 1 protecting zinc layer, 90 micron thick, 5 layers of double-component epoxy primer, 3 layers of polyurethane , white/black sectors complying with EC regulations**

Liters	bar	CODES	Valve	Diameter	Height*	Weight *
18	220	TK700140/G	Double valve	21,6 cm / 8.5"	65 cm / 25.5"	20,2 Kg / 44.5 lbs
15	232	TK700130/G/232	Double valve	20,3 cm / 8"	62 cm / 24.4"	18,2 Kg / 40 lbs
15	232	TK700130/232	Double valve	20,3 cm / 8"	62 cm / 24.4"	18,2 Kg / 40 lbs
15	232	TK700130/M/232	Single valve	20,3 cm / 8"	62 cm / 24.4"	18,2 Kg / 40 lbs
12	232	TK700120/M/232	Single valve	17,1 cm / 6.7"	67 cm / 26.3"	14,1 Kg / 31 lbs
10	200	TK700110/B	Single valve 2-2000	17,1 cm / 6.7"	57,5 cm / 22.6"	10,2 Kg / 22.4 lbs
10	200	TK700110	Single valve	17,1 cm / 6.7"	57,5 cm / 22.6"	10,2 Kg / 22.4 lbs
5	200	TK700100	Single valve	14 cm / 5.5"	44 cm / 17.3"	5,7 Kg / 12.6"
10 + 10	200	TK700150	Bibo 25 x 2	17,1 cm x 2 / 6.7" x 2	57,5 cm / 22.6"	10,2 Kg x 2 / 22.4 lbs x 2
10 + 10 with harness	200	TK700151	Bibo 25 x 2	17,1 cm x 2 / 6.7" x 2	57,5 cm / 22.6"	10,2 Kg x 2 / 22.4 lbs x 2

\* Indicative without boot and valve

